



GL Charge

Electric Vehicle Charging Stations

Home Charging Station - **Individum Lite 1.0**

1 - Phase

Individum Lite - 3,6 kW

Individum Lite - 7.2 kW



3- Phase

Individum Lite - 11 kW

Individum Lite - 22 kW



2019



Slovenia




+386 (0)40 623 988



prodaja@glcharge.com



www.glcharge.com



GL Charge

Electric Vehicle Charging Stations



Home Charging Station - **Individum Lite 1.0**

1 - Phase

Individum Lite - 3,6 kW
Individum Lite - 7.2 kW

3- Phase


Individum Lite - 11 kW
Individum Lite - 22 kW

Technical Specifications

Individum Lite 1.0			
Individum Lite 3-Phase		Individum Lite 1-Phase	
Nominal Output Power	11kW	Nominal Output Power	3,6kW
Nominal Output Voltage	400V	Nominal Output Voltage	230V
Nominal Output Current	3 x 16A	Nominal Output Current	1 x 16A
Safety Control	<ul style="list-style-type: none"> - Overcurrent Circuit Breaker - Earth Monitoring - Current Change Monitoring 	Safety Control	<ul style="list-style-type: none"> - Overcurrent Circuit Breaker - Earth Monitoring - Current Change Monitoring

General Data

Operating Temperature	-25°C to +45°C
Storage Temperature	-40°C to +80°C
Relative Humidity	Up to 98% (no condensation)
Protection	IP67 (Certificate)
Dimensions	280x180x120
Mass	3kg
Electrical Safety	IEC 61851-1, IEC 62479
Control	Mobile Application – Remote Control
Connection	Bluetooth
Certification	TUV CE



High Compatibility



Type 2 Outlet



- Remote Control by APP**
Start or stop charging via Wifi or Bluetooth
- Charging Time Setting**
Freely set the charging time and duration
- Charging History Record**
Query charging history anytime, anywhere
- Firmware Update**
Make app version upgrades
- Carbon Emission Reduction**
Check your carbon reduction by using the charging station